

DTK-SS 2000 StormShield RESIDENTIAL SURGE PROTECTION



The DITEK "StormShield" is the ultimate whole house surge protection system. The unique, modular design facilitates both ease of installation and maintenance. If a module is ever damaged by a major surge, the homeowner simply pulls out the damaged module and replaces it. The StormShield protects all power, two video feeds, and up to four phone lines. Features include LED indicators, audible alarm, surge counter and 15 AMP GFCI convenience outlet.

| FEATURES | BENEFITS |
|--|--|
| "Hot swappable" modules | Allows home owner to fully restore protection, no tools required |
| Cabinet can be surface or flush mounted | Installs like a breaker panel with ideal aesthetics |
| AC power, telephone and cable protection | Single enclosure affords complete protection to wiring exposed to harsh elements |



ONE DITEK CENTER
1720 Starkey Road,
Largo, FL 33771

1-800-753-2345
www.ditekcorp.com



General Specifications - StormShield

Agency Approvals: Wyle Labs, UL 1449, UL 497A
Service Voltage: 120/240 VAC
MCOV: 150/320 VAC
Continuous Current: Unlimited (Parallel connection) / 15 amps (GFCI receptacle)
Max. Surge Current: 225,000 Amps
Protection Modes: L-L, L-G, L-N, N-G
Warranty: Limited Lifetime Warranty
Dimension: 14.50" x 12.00" x 3.87" **Weight:** 12 lbs **Housing:** Painted Steel

Other Specifications

| | Coax | Telco |
|----------------------------|--------------------------|-----------------------------|
| Service Voltage: | <50VDC | <105VAC |
| MCOV: | 75VDC(CP-S)38VDC(S-G) | 130VAC |
| Continuous Current: | N/A | 0.150 Amps |
| Max. Surge Current: | 20,000 Amps | 9,000 Amps |
| Connection: | "F" IN/OUT (2X) | RJ11/45 |
| Protection Modes: | Center pin-Shield, S - G | Tip - Ground, Ring - Ground |

